

## Kierukkaporat DIN 338 ohennetulla varrella



Tunnus	1 24 02
DIN	338
Malli	N
Laatu	HSS
Pintakäsittely	Mustaoksidointi
Valm menetelmä	Valssattu

1 24 02	Ø	L <sup>1</sup>	L <sup>2</sup>	€
Tuotenro:	mm	mm	mm	Alv 0%
12402-10	10,00	133	87	6,70
12402-10,5	10,50	133	87	6,30
12402-11	11,00	142	94	6,30
12402-11,5	11,50	142	94	7,15
12402-12	12,00	151	101	7,15
12402-12,5	12,50	151	101	7,90
12402-13	13,00	151	101	7,90
12402-13,5	13,50	160	108	9,50
12402-14	14,00	160	108	10,00

B

1 24 02	Ø	L <sup>1</sup>	L <sup>2</sup>	€
Tuotenro:	mm	mm	mm	Alv 0%
12402-14,5	14,50	169	114	11,00
12402-15	15,00	169	114	13,00
12402-15,5	15,50	178	120	13,00
12402-16	16,00	178	120	14,00
12402-16,5	16,50	184	125	14,00
12402-17	17,00	184	125	14,00
12402-17,5	17,50	191	130	17,00
12402-18	18,00	191	130	18,00
12402-18,5	18,50	198	135	20,00
12402-19	19,00	198	135	20,00
12402-19,5	19,50	205	140	22,00
12402-20	20,00	205	140	22,00
12402-22	22,00	219	150	25,00
12402-24	24,00	246	160	28,00
12402-25	25,00	246	160	31,00

### Varren ohennus Ø

10,0 - 13,0 mm	8 mm poraistukkaan
13,5 - 16,0 mm	10 mm poraistukkaan
16,5 - 25,0 mm	13 mm poraistukkaan

## Porasarjat HSS ja HSSCO teräskoteloissa Vakiopituudet DIN 338, ja lyhyet DIN 1897



B



### Valssatut HSS, malli 1 21 02, N

Tuotenro:	Sisältö / jako / kpl	DIN-normi	€ Alv 0%
T 70 50	1,0-10,0 mm / 0,5 / 19	338	31,00
1 50 12 *	1,0-10,0 mm / 0,5 / 19	338	18,50
T 70 60	1,0-13,0 mm / 0,5 / 25	338	84,00
1 96 02	1,0-5,9 mm / 0,1 / 50	338	108,00
1 97 02	6,0-10,0 mm / 0,1 / 41	338	224,00

\* Pyöreä muovikotelo

### Hiotut HSS, malli 1 71 02, NX

Tuotenro:	Sisältö / jako / kpl	DIN-normi	€ Alv 0%
1 80 02	1,0-10,0 mm / 0,5 / 19	338	60,00
1 81 02	1,0-13,0 mm / 0,5 / 25	338	123,00
1 76 02	1,0-5,9 mm / 0,1 / 50	338	133,00
1 77 02	6,0-10,0 mm / 0,1 / 41	338	330,00
1 80 01	1,0-10,0 mm / 0,5 / 19	1897	127,00
1 81 01	1,0-13,0 mm / 0,5 / 25	1897	175,00

### Kobolttiseostetut HSSCO, malli 1 11 02, NXC

Tuotenro:	Sisältö / jako / kpl	DIN-normi	€ Alv 0%
1 75 02	1,0-10,0 mm / 0,5 / 19	338	78,00
1 73 02	1,0-13,0 mm / 0,5 / 25	338	172,00
1 59 01	1,0-5,9 mm / 0,1 / 50	338	146,00
6 10 02	6,0-10,0 mm / 0,1 / 41	338	363,00
1 75 01	1,0-10,0 mm / 0,5 / 19	1897	95,00
1 73 01	1,0-13,0 mm / 0,5 / 25	1897	222,00



### Kobolttiseostetut HSSCO, malli 1 05 02, UFL

Tuotenro:	Sisältö / jako / kpl	DIN-normi	€ Alv 0%
1 66 02	1,0-10,0 mm / 0,5 / 19	338	143,00
1 67 02	1,0-13,0 mm / 0,5 / 25	338	282,00

