

2-päiset pop-niittiporat

A



Tunnus	1 28 01
Malli	NX
Laatu	HSS
Pintakäsittely	Kirkas
Valm.menetelmä	Hiottu, ristiteroitettu

1 28 01	Ø	L ¹	L ²	€
Tuotenro:	mm	mm	mm	Alv 0%
12801-02	2,00	38	7,5	2,00
12801-02,5	2,50	43	9,5	2,00
12801-02,9	2,90	46	10,6	2,00
12801-03	3,00	46	10,6	2,00
12801-03,1	3,10	49	11,2	2,00
12801-03,2	3,20	49	11,2	2,00
12801-03,25	3,25	49	11,2	2,00
12801-03,3	3,30	49	11,2	2,00
12801-03,4	3,40	52	12,5	2,00
12801-03,5	3,50	52	12,5	2,00
12801-04	4,00	55	14,0	2,00
12801-04,1	4,10	55	14,0	2,80
12801-04,2	4,20	55	14,0	2,80
12801-04,5	4,50	58	15,5	2,80
12801-04,8	4,80	62	17,0	3,30
12801-04,9	4,90	62	17,0	3,30
12801-05	5,00	62	17,0	3,30
12801-05,1	5,10	62	17,0	3,90
12801-05,2	5,20	62	17,0	3,90
12801-05,5	5,50	66	19,0	3,90
12801-05,7	5,70	66	19,0	3,90
12801-06	6,00	66	19,0	3,90

NC-Alkureikäporat

B



Tunnus	1 4401
Witec	Norm
Kärkikulma	90°
Laatu	HSS-Co 5%
Pintakäsittely	Kirkas
Valm.menetelmä	Hiottu

1 44 01	Ø	L ¹	L ²	€
Tuotenro:	mm	mm	mm	Alv 0%
14401-04	4,00	55	12,0	6,40
14401-05	5,00	62	14,0	7,30
14401-06	6,00	66	16,0	8,70
14401-08	8,00	79	21,0	12,70
14401-10	10,00	89	25,0	19,60
14401-12	12,00	102	30,0	28,40
14401-14	14,00	107	34,0	48,00
14401-16	16,00	115	37,5	59,00
14401-20	20,00	131	45,0	94,00
14401-25	25,00	151	53,0	156,00



Tunnus	1 4501
Witec	Norm
Kärkikulma	120°
Laatu	HSS-Co 5%
Pintakäsittely	Kirkas
Valm.menetelmä	Hiottu

1 45 01	Ø	L ¹	L ²	€
Tuotenro:	mm	mm	mm	Alv 0%
14501-04	4,00	55	12,0	6,40
14501-05	5,00	62	14,0	7,30
14501-06	6,00	66	16,0	8,70
14501-08	8,00	79	21,0	12,70
14501-10	10,00	89	25,0	19,60
14501-12	12,00	102	30,0	28,40
14501-14	14,00	107	34,0	48,00
14501-16	16,00	115	37,5	59,00
14501-20	20,00	131	45,0	94,00
14501-25	25,00	151	53,0	156,00